

HULL

- Color - Oyster gel coat hull w/colored inset & waterline
- Structural lamination multi-directional knitted fiberglass w/ vinylester skin coat
- Stringers – Fiberglass encapsulated full length composite stringers
- Boarding platform with stainless steel through bolted brackets and under mounted telescopic swim ladder
- Hull Guards - UV-stabilized black PVC-guards: anchor, and sheer-guard w/316 Stainless Steel inset
- Fasteners - All exterior fasteners 316 Stainless Steel
- Bottom Paint – Eco friendly ablative antifouling (2 coats/black)
- Bilge Pumps - 2000 GPH in 2 compartments & 500 gph forward with auto/manual switches at helm
- Bonding System -anodes on transom, rudder, and shoe

DECK

- Color - Oyster gel coat
- Deck - Molded textured surface in walking & work areas
- Deck - Raised side decks
- Drains - cockpit
- Anchor Roller Assembly
- Windlass - 1000W controlled at helm and foot controls
- Bow Bitt - 316 stainless steel Samson post
- Storage - Deck hatch to lazarette w/sealing gasket
- Deck Rails - Deck, 1" bow and stern
- Deck Box - hinged w/LPG 11# tank
- Hand Rails - 1" 316 stainless steel full length hand rails over pilot house doors and each side of salon roof
- Hand Grab - 316 SS on transom over swim ladder
- Windows - DIAMOND SEA GLAZE® Oyster powder- coated finish, sliding windows in salon and pilothouse
- Doors - DIAMOND SEA GLAZE® Oyster powder-coated: two sliding pilot house entry and one aft hatch style entry door w/drop sliding window and screen
- Portlights - 8" round stainless steel w/screens (2)
- Cleats - 8" cap rail mounted 316 stainless steel mooring cleats (6) w/chocks (2)
- Deck Fittings, 316 stainless steel - 2" fuel fill, 1-1/2" water fill, 1-1/2" waste suction
- Pennant Staff receiver - in bow rail
- Lazarette vents, polished Stainless Steel

PROPULSION / ENGINE ROOM

- Engine – Single Volvo D3-150hp, 3000 rpm diesel
- Alternator – 110 amp (12v)
- Fuel Filter - Primary 10 micron element secondary two micron element on the engine
- Exhaust - 3" horizontal water lift muffler, transom exit
- Propeller – Bronze 4-blade LH, tuned to Class 1 ISO-484 pitch tolerances
- Propeller Shaft - 1.50" stainless steel w/PSS® drip-less shaft seal
- Seawater Strainers - bronze
- Potable Water Pump – 12v Variable pressure
- Lights - engine room (2) LED
- Sound Insulation – Hush kit, 1" barrier silver mylar
- Outlet – 110VAC GFCI

HEATING

- Heating System - Hydronic heat off engine with three outlets

GALLEY

- Cooktop - 2-burner propane
- Refrigerator, Nova Kool® R2600 12vDC undercounter - [2.4cf / 68L] w/stainless steel face
- Countertop – Acrylic solid surface w/ sea rail
- Sink - stainless steel, mirror finish single bowl w/faucet
- Cabinets – Sapele faced
- Storage Locker
- Drawers - full extension ball bearing tracks & sea locks w/sapele faces
- Lights - Overhead, 12VDC LED (2)

COMPANIONWAY

- Lighted Storage locker 110VAC outlet, 12VDC/USB

SALON

- Dinette, Convertible to full berth w/ removeable storage bins underneath, laminated table & sapele sea rail
- Outlets – 110VAC, 12VDC/ USB
- Lights - Overhead, 12VDC LED (2)
- Fusion Stereo with 2 speakers, & 2 in the cockpit

PILOT HOUSE

- Helm seats - fixed w/foot rest
- Overhead Instrument Console
- Engine Control – Electronic single lever shift/ throttle
- Engine Monitoring – Volvo 7" LCD digital display panel: water temp, oil pressure, voltmeter & tachometer
- Bow Thruster Control – joystick
- Compass - binnacle
- Windshield wipers - pantograph style, on/off (3)
- Fan - 12VDC
- Power Port - 12VDC/ USB

FORWARD CABIN (FOC'SLE)

- Offset full berth – upholstered foam mattress w/storage under
- Chain locker forward with access hatch
- Lights - Reading, 12VDC LED (2)
- Hatch - 16" with screen

HEAD COMPARTMENT

- Toilet – Tecma® Easy Fit electric fresh water flush low water flow [comfort height]
- Molded one-piece head unit w/fiberglass sink and faucet/shower wand
- Shower - curtain & track, textured shower sole
- Mirror - On door
- Fixtures - towel ring, toilet paper holder & robe hook
- Door - Sapele entry with latch
- Lights - Overhead, LED
- Outlet - 110VAC GFCI

INTERIOR FINISH AND TRIM

- Upholstery – choice of colors (see samples)
- Carpet – standard color
- Cabinet Tops – acrylic solid surface tops with sea rail trim
- Sapele trim & doors
- Overhead and bulkhead covering – vinyl
- Walls – vinyl

LAZARETTE

- Gel coated and ventilated
- Steering gear
- Storage space

STEERING SYSTEM

- Steering System - manual hydraulic
- Rudder and Shoe – stainless steel w/sacrificial anode
- Rudder port bearing and shaft lip seal
- Tiller Arm - Bronze w/rudder stops
- Helm Wheel – Hardwood w/ stainless steel accents
- Valves and fittings for autopilot hydraulic pump connection
- Bow Thruster - SIDE-POWER® SE40/125S 88lbs/40kg of Thrust

12V DC ELECTRICAL SYSTEM

- Battery, Start - 12V AGM Group-31 w/box, 100 amp hours
- Batteries, House - 6V AGM deep cycle golf-cart type (2) w/boxes, 220 amp hours
- Breaker Panel 12VDC - BLUE SEAS 360® w/LED lights
- Battery selector - BLUE SEAS® rotary switch
- Wire - marine grade tinned copper throughout

110V AC ELECTRICAL SYSTEM

- Shore power connection - SMARTPLUG® 30A, with 50' cord, starboard
- Breaker panel - BLUE SEAS® 360 panel 110VAC with LED lights ELCI main circuit breaker w/digital multi-meter

SAFETY PACKAGE

- Fire Extinguishers, (1) 5 LB and (2) 2 LB
- High bilge water alarm
- Smoke detector in each cabin & central seating area
- Radar reflector - located in stack
- Horn - Single Electric
- Light - Anchor, LED, USCG approved
- Lights - Navigation, LED, USCG approved
- NMMA Certification to ABYC Standards
- Canadian Declaration of Conformity

TANKAGE

- Potable Water Polyethylene – 40 gallon in two tanks w/crossover line
- Fuel Tank – 100 gallon with sight tube
- Gray Water Sump for shower 800GPH
- Black Water – 20 gallon in keel, w/ deck pump out
- Tank Monitoring – Digital all liquids at helm
- Tank Monitoring - Black water alarm light "full" at head
- Heater, Water - 6-gallon electric/engine heat

DIMENSIONS

- Length Overall - 28' 9" / 8.76m (w/swim platform & bow roller)
- Waterline length – 26' 4"
- Beam - 9' 6" / 2.89m
- Draft - 3' 3" / 0.99m
- Displacement Weight - 8,500 lbs / 3,859kg
- Height above waterline – 8' 7" to stack
- Headroom - Forward Cabin 6' 0" / 1.83m
- Headroom - Pilot House 6' 2" / 1.88m
- Headroom - Salon 6' 4" / 1.93m

OWNER'S PACKAGE

- Engine & Reduction Gear manuals
- Component owner's manuals - w/Electrical Schematics
- Nordic Tug Operators Manual
- 10-micron fuel filter element for main engine RACOR®
- Matched gel coat touch-up kit
- Multi-Bit Screwdriver & Stainless Steel Deck Fitting Key
- Fenders & lines

COMMISSIONING PACKAGE

- Shaft Seal Collar O-Ring Kit
- Container box w/Lid